



Shaped Coolant Hose

COOLMASTER- 300 SERIES: SHAPED COOLANT HOSE (SILICONE – GLOSSY)

Sr.	Part No	Hose ID		Arm Length		Wall thickness		Outer Diameter		Burst Pressure as per		Burst Pressure as per	
										SAE J20 (Heavy-Duty standard wall)		SAE J20 (Heavy-Duty standard wall)	
										(Mpa)		(PSI)	
		MM	INCH	MM	INCH	MM	INCH	MM	INCH	Specification	Actual	Specification	Actual
1	300-039-060	10	0.39	152.4	6	4.95	0.19	19.9	0.78	3.29	3.8	477	551
2	300-050-060	13	0.5	152.4	6	4.95	0.19	22.9	0.9	2.93	3	425	435
3	300-063-060	16	0.63	152.4	6	4.95	0.19	25.9	1.02	2.59	3.11	376	451
4	300-075-060	19	0.75	152.4	6	4.95	0.19	28.9	1.14	2.24	2.64	325	383
5	300-087-060	22	0.87	152.4	6	4.95	0.19	31.9	1.26	2.24	2.35	325	340
6	300-100-060	25	1	152.4	6	4.95	0.19	34.9	1.37	2.06	2.26	299	327
7	300-114-060	29	1.14	152.4	6	4.95	0.19	38.9	1.53	2.06	2.1	299	305
8	300-125-060	32	1.25	152.4	6	4.95	0.19	41.9	1.65	1.90	2	276	290
9	300-138-060	35	1.38	152.4	6	4.95	0.19	44.9	1.77	1.90	1.98	276	287
10	300-150-060	38	1.5	152.4	6	4.95	0.19	47.9	1.89	1.72	1.94	249	281
11	300-161-060	41	1.61	152.4	6	4.95	0.19	50.9	2	1.72	1.92	249	278
12	300-175-060	44	1.73	152.4	6	4.95	0.19	53.9	2.12	1.55	1.89	225	274
13	300-200-060	51	2	152.4	6	4.95	0.22	60.9	2.4	1.38	1.6	200	200
14	300-225-060	57	2.24	152.4	6	4.95	0.19	66.9	2.63	1.21	1.28	175	186
15	300-236-060	60	2.36	152.4	6	4.95	0.19	69.9	2.75	1.21	1.24	175	180
16	300-250-060	64	2.5	152.4	6	4.95	0.19	73.9	2.91	1.03	1.17	149	169
17	300-275-070	70	2.76	177.8	7	4.95	0.19	79.9	3.15	0.86	1.1	125	160
18	300-300-075	76	3	190.5	7.5	4.95	0.19	85.9	3.38	0.60	1.08	87	157
19	300-325-075	83	3.27	190.5	7.5	4.95	0.19	92.9	3.66	0.60	0.93	87	135
20	300-350-085	89	3.5	215.9	8.5	4.95	0.19	98.9	3.89	0.52	0.9	75	100
21	300-400-095	102	4	241.3	9.5	5.5	0.22	113	4.45	0.34	0.61	49	88
22	300-500-095	127	5	241.3	9.5	5.5	0.22	138	5.43	0.34	0.52	49	75

