



Straight Coolant Hose With Wire

Available in 3ft 6ft and 12ft

COOLMASTER 200 SERIES: STRAIGHT COOLANT HOSE WITH WIRE (SILICONE – GLOSSY)

Sr. No	Part Number	Hose Inner Diameter		Outer Diameter		Burst Pressure		Burst Pressure		Vacuum Pressure	
						(Mpa)		(PSI)		(Kpa)	
		MM	INCH	MM	INCH	Specification	Actual	Specification	Actual	Specification	Actual
1	200-039	10	0.39	19.9	0.78	2.06	5.03	299	730	84.4	> 92
2	200-050	13	0.50	22.9	0.90	2.06	4.97	299	721	84.4	> 92
3	200-063	16	0.63	25.9	1.02	2.06	3.81	299	553	84.4	> 92
4	200-075	19	0.75	28.9	1.14	2.06	3.72	299	540	84.4	> 92
5	200-087	22	0.87	31.9	1.26	2.06	3.23	299	468	84.4	> 92
6	200-100	25	1.00	34.9	1.37	2.06	2.84	299	412	84.4	> 92
7	200-114	29	1.14	38.9	1.53	1.90	2.82	276	409	84.4	> 92
8	200-125	32	1.26	41.9	1.65	1.90	2.77	276	402	84.4	> 92
9	200-138	35	1.38	44.9	1.77	1.90	2.42	276	351	84.4	> 92
10	200-150	38	1.50	47.9	1.89	1.72	2.28	249	331	84.4	> 92
11	200-161	41	1.61	50.9	2.00	1.72	2.07	249	300	84.4	> 92
12	200-175	44	1.73	53.9	2.12	1.55	1.87	225	271	84.4	> 92
13	200-200	51	2.00	60.9	2.40	1.38	1.55	200	225	84.4	> 92
14	200-225	57	2.24	66.9	2.63	1.21	1.42	175	206	84.4	> 92
15	200-236	60	2.36	69.9	2.75	1.21	1.38	175	200	84.4	> 92
16	200-250	64	2.50	73.9	2.91	1.03	1.36	149	197	84.4	> 92
17	200-275	70	2.76	79.9	3.15	0.86	1.28	125	186	84.4	> 92
18	200-300	76	3.00	85.9	3.38	0.69	1.12	100	162	84.4	> 92
19	200-325	83	3.27	92.9	3.66	0.52	1.08	75	157	84.4	> 92
20	200-350	89	3.50	98.9	3.89	0.52	1.06	75	154	84.4	> 92
21	200-400	102	4.00	111.9	4.41	0.34	0.94	49	136	84.4	> 92

