



Straight Coolant Hose

Available in 3ft 6ft and 12ft

[CONTENTS PAGE >](#)

COOLMASTER 100 SERIES: STRAIGHT COOLANT HOSE (SILICONE – GLOSSY)

no of Plies	Part No	Hose ID		Wall thickness		Outer Diameter		Burst Pressure (Mpa)		Burst Pressure (PSI)	
		MM	INCH	MM	INCH	MM	INCH	Specification	Actual	Specification	Actual
3	100-039	10	0.39	4.95	0.19	19.9	0.78	3.29	4.23	477	614
3	100-050	13	0.50	4.95	0.19	22.9	0.9	2.93	3.05	425	442
3	100-063	16	0.63	4.95	0.19	25.9	1.02	2.59	2.99	376	434
3	100-075	19	0.75	4.95	0.19	28.9	1.14	2.24	2.45	325	355
4	100-087	22	0.87	4.95	0.19	31.9	1.26	2.24	2.32	325	336
4	100-100	25	1.00	4.95	0.19	34.9	1.37	2.06	2.28	299	331
4	100-114	29	1.14	4.95	0.19	38.9	1.53	2.06	2.16	299	313
4	100-125	32	1.26	4.95	0.19	41.9	1.65	1.90	1.98	276	287
4	100-138	35	1.38	4.95	0.19	44.9	1.77	1.90	1.92	276	278
4	100-150	38	1.50	4.95	0.19	47.9	1.89	1.72	1.86	249	270
4	100-161	41	1.61	4.95	0.19	50.9	2.00	1.72	1.78	249	258
4	100-175	44	1.73	4.95	0.19	53.9	2.12	1.55	1.62	225	235
4	100-188	48	1.88	4.95	0.19	57.1	2.25	1.38	1.60	200	232
4	100-200	51	2.00	5.5	0.22	62	2.44	1.38	1.59	200	200
4	100-213	54	2.13	4.95	0.19	65	2.56	1.38	1.52	200	230
4	100-225	57	2.24	4.95	0.19	66.9	2.63	1.21	1.32	175	191
4	100-236	60	2.36	4.95	0.19	69.9	2.75	1.21	1.26	175	182
4	100-250	64	2.50	4.95	0.19	73.9	2.91	1.03	1.14	149	165
4	100-263	67	2.63	4.95	0.19	76.7	3.02	1.03	1.12	149	162
4	100-275	70	2.76	4.95	0.19	79.9	3.15	0.86	1.10	125	160
4	100-288	73	2.88	4.95	0.19	83.05	3.27	0.86	1.08	125	156
4	100-300	76	3.00	4.95	0.19	85.9	3.38	0.60	0.95	87	138
4	100-325	83	3.27	4.95	0.19	92.9	3.66	0.60	0.84	87	122
4	100-350	89	3.50	4.95	0.19	98.9	3.89	0.52	0.75	75	108
4	100-375	95	3.75	4.95	0.19	105.15	4.14	0.52	0.72	75	104
5	100-400	102	4.00	5.5	0.22	113	4.45	0.34	0.63	49	92

